



# Material Safety Data Sheet

## SPB Adhesive

### Section 1: Identification of the Product and Company Identification

Product Name: RubberBond SPB Adhesive

Use of Substance: Adhesive

Suppliers Details: Flex-R Ltd.

Sandswood House,  
Hillbottom Road,  
Sands Industrial Estate,  
High Wycombe,  
Buckinghamshire.  
HP12 4HJ

Tel: 01494 448792 Fax: 01494 858433 Email: [enq@rubberbond.co.uk](mailto:enq@rubberbond.co.uk)

### Section 2: Hazards Identification

#### 2.1. Classification of the substance or mixture

**Classification under CHIP:** F+: R12; Xi: R38; N: R51/53

**Classification under CLP:** Acute Tox. 4: H302; Acute Tox. 3: H331; Aquatic Chronic 2: H411; Flam.

Aerosol 1: H222; Repr. 2: H361d; Skin Irrit. 2: H315; STOT SE 3: H336

**Most important adverse effects:** Extremely flammable. Irritating to skin. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

#### Label elements under CLP:

**Hazard statements:** H222: Extremely flammable aerosol.

H302: Harmful if swallowed.

H315: Causes skin irritation.

H331: Toxic if inhaled.

H336: May cause drowsiness or dizziness.

H361d: Suspected of damaging the unborn child.

H411: Toxic to aquatic life with long lasting effects.

**Signal words:** Danger

**Hazard pictograms:** GHS02: Flame

GHS06: Skull and crossbones

GHS08: Health hazard

GHS09: Environmental



**Precautionary statements:** P211: Do not spray on an open flame or other ignition source.

P251: Pressurized container: Do not pierce or burn, even after use.

P260: Do not breathe.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P301+310: IF SWALLOWED: Immediately call a POISON CENTER or doctor.

P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

**Exclusive British Isles Distributors for Carlisle-SynTec and RubberBond EPDM single ply roofing materials.**

Flex-R Ltd, Sandswood House, Hillbottom Road, Sands Industrial Estate, High Wycombe,  
Bucks ,HP12 4HJ. Tel: +44 (0)1494 448792 Fax: +44 (0)1494 858433





# Material Safety Data Sheet

## SPB Adhesive

### 2.2. Label elements

#### Label elements under CHIP:

**Hazard symbols:** Extremely flammable.

Irritant.

Dangerous for the environment.



**Risk phrases:** R12: Extremely flammable.

R38: Irritating to skin.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Safety phrases:** S16: Keep away from sources of ignition - No smoking.

S17: Keep away from combustible material.

S24/25: Avoid contact with skin and eyes.

S36/37: Wear suitable protective clothing and gloves.

S38: In case of insufficient ventilation, wear suitable respiratory equipment.

S61: Avoid release to the environment. Refer to special instructions / safety data sheets.

**Precautionary phrases:** Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

### 2.3. Other hazards

**Other hazards:** In use, may form flammable / explosive vapour-air mixture.

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

Hazardous ingredients:

HYDROCARBONS, C6-C7, N-ALKANES, ISOALKANES, CYCLICS, <5% N-HEXANE

EINECS	CAS	CHIP Classification	CLP Classification	Percent
-	-	Xn: R65; Xi: R38; F: R11; N: R51/53	Flam. Liq. 2: H225; Asp. Tox. 1: H304; Aquatic Chronic 2: H411; Skin Irrit. 2: H315; STOT SE 3: H336	30-50%

DIMETHYL ETHER

204-065-8	115-10-6	F+: R12 Substance with a community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	30-50%
-----------	----------	---	-------------------------------------	--------

TOLUENE - REACH registered number(s): 01-2119471310-51

203-625-9	108-88-3	F: R11; Xi: R38; Xn: R48/20; Xn: R63; Xn: R65; -: R67	Flam. Liq. 2: H225; Repr. 2: H361d; Asp. Tox. 1: H304; STOT RE 2: H373; Skin Irrit. 2: H315; STOT SE 3: H336	1-10%
-----------	----------	---	--	-------

**Exclusive British Isles Distributors for Carlisle-SynTec and RubberBond EPDM single ply roofing materials.**

Flex-R Ltd, Sandswood House, Hillbottom Road, Sands Industrial Estate, High Wycombe, Bucks, HP12 4HJ. Tel: +44 (0)1494 448792 Fax: +44 (0)1494 858433





# Material Safety Data Sheet

## SPB Adhesive

### ACETONE

200-662-2	67-64-1	F: R11; Xi: R36; -: R66; -: R67	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	1-10%
-----------	---------	---------------------------------	--	-------

### N-HEXANE - REACH registered number(s): 01-2119480412-44-0000

203-777-6	110-54-3	F: R11; Xi: R38; Xn: R48/20; Xn: R62; Xn: R65; -: R67; N: R51/53	Flam. Liq. 2: H225; Repr. 2: H361f; Asp. Tox. 1: H304; STOT RE 2: H373; Skin Irrit. 2: H315; STOT SE 3: H336; Aquatic Chronic 2: H411	1-10%
-----------	----------	--	---	-------

### METHYL ACETATE

201-185-2	79-20-9	F: R11; Xi: R36; -: R66; -: R67	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	1-10%
-----------	---------	---------------------------------	--	-------

## Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** Remove from skin with paper or towel. Wash effected area thoroughly with soap and water. Seek medical advice if symptoms persist.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Wash out mouth with water. Consult a doctor.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor if symptoms persist.

### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:** Show this safety data sheet to the doctor in attendance.

## Section 5: Fire-fighting measures

### 5.1. Extinguishing media

**Extinguishing media:** Alcohol resistant foam. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture. Vapour may travel considerable distance to source of ignition and flash back.

### 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Exclusive British Isles Distributors for Carlisle-SynTec and RubberBond EPDM single ply roofing materials.

Flex-R Ltd, Sandswood House, Hillbottom Road, Sands Industrial Estate, High Wycombe, Bucks ,HP12 4HJ. Tel: +44 (0)1494 448792 Fax: +44 (0)1494 858433





# Material Safety Data Sheet

## SPB Adhesive

### Section 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

#### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

#### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

#### 6.4. Reference to other sections

**Reference to other sections:** Refer to section 8 of SDS.

### Section 7: Handling and storage

#### 7.1. Precautions for safe handling

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is forbidden. Use non-sparking tools.

#### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build-up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition.

**Suitable packaging:** Must only be kept in original packaging.

#### 7.3. Specific end use(s)

**Specific end use(s):** No data available.

### Section 8: Exposure controls/personal protection

#### 8.1. Control parameters

**Hazardous ingredients: DIMETHYL ETHER**

Workplace exposure limits:			Respirable dust	
State	8 Hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	766 mg/m <sup>3</sup>	958 mg/m <sup>3</sup>	-	-

#### TOLUENE

UK	191 mg/m <sup>3</sup>	384 mg/m <sup>3</sup>	-	-
----	-----------------------	-----------------------	---	---

#### ACETONE

UK	1210 mg/m <sup>3</sup>	3620 mg/m <sup>3</sup>	-	-
----	------------------------	------------------------	---	---

Exclusive British Isles Distributors for Carlisle-SynTec and RubberBond EPDM single ply roofing materials.

Flex-R Ltd, Sandswood House, Hillbottom Road, Sands Industrial Estate, High Wycombe, Bucks ,HP12 4HJ. Tel: +44 (0)1494 448792 Fax: +44 (0)1494 858433





# Material Safety Data Sheet

## SPB Adhesive

### N-HEXANE

UK	72 mg/m3	-	-	-
----	----------	---	---	---

### METHYL ACETATE

UK	616 mg/m3	770 mg/m3	-	-
----	-----------	-----------	---	---

### DNEL/PNEC Values

DNEL / PNEC No data available.

### 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

**Respiratory protection:** If exposure levels are likely to be exceeded, use a full face mask fitted with an organic AXP3 filter for short term low level exposures. For long term or high level exposures, compressed airline breathing apparatus should be used.

**Hand protection:** Avoid skin contact. For repeated exposure use Viton or 4H chemical gloves. for low exposure use nitrile gloves. The user has a legal duty to carry out a COSHH risk assessment to determine the correct glove.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Protective clothing.

**Environmental:** No special requirement.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**State:** Aerosol

**Colour:** Amber

**Evaporation rate:** Fast

**Oxidising:** Non-oxidising (by EC criteria)

**Solubility in water:** Insoluble

**Viscosity:** Non-viscous

**Boiling point/range °C:** 60 **Flammability limits %:** lower: 0.6 upper: 13

**Flash point °C:** -29

**Auto flammability °C:** 275

**Relative density:** 0.81

### 9.2. Other information

**Other information:** No data available.

## Section 10: Stability and Reactivity

### 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

**Chemical stability:** Stable under normal conditions. Stable at room temperature.

### 10.3. Possibility of hazardous reactions

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions. Decomposition may occur on exposure to conditions or materials listed below.

### 10.4. Conditions to avoid

**Conditions to avoid:** Heat. Hot surfaces. Sources of ignition. Flames.

Exclusive British Isles Distributors for Carlisle-SynTec and RubberBond EPDM single ply roofing materials.

Flex-R Ltd, Sandswood House, Hillbottom Road, Sands Industrial Estate, High Wycombe, Bucks ,HP12 4HJ. Tel: +44 (0)1494 448792 Fax: +44 (0)1494 858433





### 10.5. Incompatible materials

**Materials to avoid:** Strong oxidising agents. Strong acids.

### 10.6. Hazardous decomposition products

**Haz. decomp. products:** In combustion emits toxic fumes.

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

Route	Species	Test	Value	Units
VAPOURS	RAT	4H LC50	>5	mg/l
ORAL	RAT	LD50	>2000	mg/kg
DERMAL	RBT	LD50	>2000	mg/kg

#### Hazardous ingredients:

##### TOLUENE

DERMAL	RBT	LD50	>2000	mg/kg
IVN	RAT	LD50	1960	mg/kg
ORAL	RAT	LD50	>2000	mg/kg
ORL	MUS	LD50	2	gm/kg
ORL	RAT	LD50	6900	mg/kg
VAPOURS	RAT	4H LC50	>20	mg/l

##### ACETONE

IVN	RAT	LD50	5500	mg/kg
ORL	MUS	LD50	3000	mg/kg
ORL	RAT	LD50	5800	mg/kg

##### N-HEXANE

IPR	RAT	LDLO	9100	mg/kg
IVN	MUS	LDLO	831	mg/kg
ORL	RAT	LD50	25	gm/kg

##### METHYL ACETATE

ORL	RAT	LD50	>5	gm/kg
ORL	RAT	LD50	8	gm/kg

#### Relevant effects for mixture:

Effect	Route	Basis
Irritation	DRM	Hazardous: calculated

#### Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

**Other information:** Not applicable.



# Material Safety Data Sheet

## SPB Adhesive

### Section 12: Ecological Information

#### 12.1. Toxicity

##### Ecotoxicity values:

Species	Test	Value	Units
FISH	96H LC50	>1-10	mg/l
ALGAE	96H LC50	>1-10	mg/l

#### 12.2. Persistence and degradability

**Persistence and degradability:** Biodegradable in part only.

#### 12.3. Bioaccumulative potential

**Bioaccumulative potential:** Bioaccumulation potential.

#### 12.4. Mobility in soil

**Mobility:** Readily absorbed into soil.

#### 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

#### 12.6. Other adverse effects

**Other adverse effects:** Toxic to aquatic organisms.

### Section 13: Disposal considerations

#### 13.1. Waste treatment methods

**Disposal operations:** Wet waste: Arrange for disposal by a licenced waste disposal company

**Disposal of packaging:** Arrange for disposal by a licenced waste disposal company

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

### Section 14: Transport information

#### 14.1. UN number

**UN number:** UN3501

#### 14.2. UN proper shipping name

**Shipping name:** CHEMICAL UNDER PRESSURE, FLAMMABLE, N.O.S

#### 14.3. Transport hazard class(es)

**Transport class:** 2

#### 14.4. Environmental hazards

**Environmentally hazardous:** Yes

**Marine pollutant:** No

#### 14.5. Special precautions for user

**Special precautions:** No special precautions.

**Tunnel code:** B/D

**Transport category:** 2

Exclusive British Isles Distributors for Carlisle-SynTec and RubberBond EPDM single ply roofing materials.

Flex-R Ltd, Sandswood House, Hillbottom Road, Sands Industrial Estate, High Wycombe, Bucks ,HP12 4HJ. Tel: +44 (0)1494 448792 Fax: +44 (0)1494 858433







### Section 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**Specific regulations:** This product is classified as a mixture. CLP classification for information only.

#### 15.2. Chemical Safety Assessment

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

### Section 16: Other information

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010. \* indicates text in the SDS which has changed since the last revision. rev 2 changes: chemical listed: HYDROCARBONS, C6-C7, N-ALKANES, ISOALKANES, CYCLICS, <5% N-HEXANE - additional phrases: R38, R52/53

**Phrases used in s.2 and s.3:** EUH066: Repeated exposure may cause skin dryness or cracking.  
H220: Extremely flammable gas.  
H222: Extremely flammable aerosol.  
H225: Highly flammable liquid and vapour.  
H302: Harmful if swallowed.  
H304: May be fatal if swallowed and enters airways.  
H315: Causes skin irritation.  
H319: Causes serious eye irritation.  
H331: Toxic if inhaled.  
H336: May cause drowsiness or dizziness.  
H361d: Suspected of damaging the unborn child.  
H361f: Suspected of damaging fertility.  
H373: May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.  
H411: Toxic to aquatic life with long lasting effects.  
R11: Highly flammable.  
R12: Extremely flammable.  
R36: Irritating to eyes.  
R38: Irritating to skin.  
R48/20: Harmful: danger of serious damage to health by prolonged exposure through inhalation.  
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R62: Possible risk of impaired fertility.  
R63: Possible risk of harm to the unborn child.  
R65: Harmful: may cause lung damage if swallowed.  
R66: Repeated exposure may cause skin dryness or cracking.  
R67: Vapours may cause drowsiness and dizziness.

**Legal disclaimer:** The above information supplied in this MSDS is designed only as guidance for the safe use, storage and handling of the product. The information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

**Exclusive British Isles Distributors for Carlisle-SynTec and RubberBond EPDM single ply roofing materials.**

Flex-R Ltd, Sandswood House, Hillbottom Road, Sands Industrial Estate, High Wycombe, Bucks ,HP12 4HJ. Tel: +44 (0)1494 448792 Fax: +44 (0)1494 858433

