



Safety Data Sheet

Two-Part Pourable Sealer – Part A 3.78L

Revision Date: 28/02/2018

Section 1: Identification of the Product and Company Identification

1.1. Product Identifier

Product Name: RubberBond Two-Part Pourable Sealer – Part A
Product Code: 302084

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Waterproof sealant. Product for industrial use only
Uses advised against No additional information available

1.3. Details of the supplier of the safety data sheet

Suppliers: Flex-R
Sandswood House
Hillbottom Road
Sands Industrial Estate
High Wycombe
Buckinghamshire
HP12 4HJ
Tel: 01494 448792 Fax: 01494 858433 Email: enq@rubberbond.co.uk

1.4. Emergency telephone number

Emergency telephone 01494 448792 (NOT 24HRS Monday-Thursday 08.30 – 17.30
Friday 08.30 – 16.30)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards No additional information available
Health hazards Carc. 1B H350 Repr. 2 H361d STOT RE 1 H372
Environmental hazards No additional information available
Human Health No additional information available
Physicochemical No additional information available

2.2. Label elements

Pictogram



Exclusive British Isles Distributors for Carlisle-SynTec and RubberBond EPDM single ply roofing materials.

Flex-R, Sandswood House, Hillbottom Road, Sands Industrial Estate, High Wycombe, Buckinghamshire, HP12 4HJ. Tel: +44 (0)1494 448792 Fax: +44 (0)1494 858433





Safety Data Sheet

Two-Part Pourable Sealer – Part A 3.78L

Revision Date: 28/02/2018

Signal word

Danger

Hazard statements

H350 - May cause cancer
H361d - Suspected of damaging the unborn child
H372 - Causes damage to organs (adrenal glands, bone marrow, liver, kidneys, lymphoid system, stomach, thymus) through prolonged or repeated exposure (in contact with skin)

Precautionary statements

P201 - Obtain special instructions before use
P260 - Do not breathe vapours
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P308+P313 - IF exposed or concerned: Get medical advice/attention
P405 - Store locked up
P501 - Dispose of contents/container to an authorised waste collection point

Contains

Distillates (petroleum), hydrotreated heavy naphthenic

2.3. Other hazards

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

SECTION 3: Composition/information on ingredients

3.2. Mixtures

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC	20 - 50%	
CAS number: 64742-52-5	EC number: 265-155-0	REACH registration number:
	EC Index number: 649-465-00-7	
Classification Carc. 1B, H350 Repr. 2, H361d STOT RE 1, H372 Asp. Tox. 1, H304		
CALCIUM CARBONATE	10 - 30%	
CAS number: 1317-65-3	EC number: 215-279-6	REACH registration number:
Classification Not classified		
1,1'-PHENYLIMINODIPROPAN-2-OL	3 - 10%	
CAS number: 3077-13-2	EC number: 221-360-7	REACH registration number:
Classification Eye Irrit. 2, H319		

Exclusive British Isles Distributors for Carlisle-SynTec and RubberBond EPDM single ply roofing materials.

Flex-R, Sandwood House, Hillbottom Road, Sands Industrial Estate, High Wycombe, Buckinghamshire, HP12 4HJ. Tel: +44 (0)1494 448792 Fax: +44 (0)1494 858433





Safety Data Sheet

Two-Part Pourable Sealer – Part A 3.78L

Revision Date: 28/02/2018

CARBON BLACK	1 - 5%	
CAS number: 1333-86-4	EC number: 215-609-9	REACH registration number:
Classification Not classified		

SYNTHETIC CRYSTALLINE-FREE GEL	1 - 5%
CAS number: 112926-00-8	REACH registration number:
Classification Skin Irrit. 2, H315	

The Full Text for all Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If symptoms develop, obtain medical attention.
Ingestion	Do NOT induce vomiting. Rinse mouth. Give 100 - 200 ml of water to drink. Do not give an unconscious person anything to drink. Obtain immediate medical attention.
Skin contact	Immediately remove contaminated clothing or footwear. Rinse skin with plenty of water or shower. If skin irritation occurs: Get medical advice/attention.
Eye contact	Rinse cautiously with water for several minutes. Ensure that folded skin of eyelids is thoroughly washed with water. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	Inhalation of vapours may cause respiratory irritation.
Ingestion	Ingestion may cause irritation of the gastrointestinal tract.
Skin contact	May cause slight irritation.
Eye contact	May cause slight irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
-----------------------------	------------------------

Exclusive British Isles Distributors for Carlisle-SynTec and RubberBond EPDM single ply roofing materials.

Flex-R, Sandwood House, Hillbottom Road, Sands Industrial Estate, High Wycombe, Buckinghamshire, HP12 4HJ. Tel: +44 (0)1494 448792 Fax: +44 (0)1494 858433





Safety Data Sheet

Two-Part Pourable Sealer – Part A 3.78L

Revision Date: 28/02/2018

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Dry chemical. Foam. Carbon dioxide.
Unsuitable extinguishing media	Do not use water jet. Water may be ineffective.

5.2. Special hazards arising from the substance or mixture

Fire hazard	Not flammable. Product can burn if exposed to open flames or high temperatures. Vapours are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapours.
Explosion hazard	Containers may rupture when heated.
Hazardous decomposition products in case of fire	Fire may produce irritating, corrosive and/or toxic gases. Butadiene. calcium oxides. Carbon monoxide. Carbon dioxide.

5.3. Advice for firefighters

Firefighting instructions	Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Do not allow run-off from firefighting to enter drains or water courses.
Special protective equipment for firefighters	Fire fighters should wear complete protective clothing including self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures	Evacuate unnecessary personnel. Ensure adequate ventilation.
-----------------------------	--

6.1.2. For emergency responders

Protective equipment	Wear suitable protective clothing and eye or face protection.
Emergency procedures	Ensure adequate ventilation. Avoid inhalation of vapours. Avoid contact with skin and eyes.

6.2. Environmental precautions

Environmental precautions	Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if large amounts of the product enters sewers or public waters.
----------------------------------	---

6.3. Methods and material for containment and cleaning up

Exclusive British Isles Distributors for Carlisle-SynTec and RubberBond EPDM single ply roofing materials.

Flex-R, Sandwood House, Hillbottom Road, Sands Industrial Estate, High Wycombe, Buckinghamshire, HP12 4HJ. Tel: +44 (0)1494 448792 Fax: +44 (0)1494 858433

4/11





Safety Data Sheet

Two-Part Pourable Sealer – Part A 3.78L

Revision Date: 28/02/2018

Methods for cleaning up

Absorb with earth, sand or other non-combustible material, allow to cure, and transfer to containers for later disposal. Wash spill area with soapy water. Washings must be prevented from entering surface water drains.

6.4. Reference to other sections

Reference to other sections SECTION 8: Exposure controls/personal protection. SECTION 13: Disposal considerations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Provide adequate ventilation. Avoid inhalation of vapours. Avoid contact with skin, eyes and clothing.

Hygiene measures Do not eat, drink or smoke when using this product. Handle in accordance with good industrial hygiene and safety practice. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions Store locked up. Store in a well-ventilated place. Keep container tightly closed. Protect from freezing.

Incompatible materials Strong acids. Strong alkalis. Strong oxidizing agents.

Storage temperature 0 - 30 °C

7.3. Specific end use(s)

Specific end use(s) Waterproof sealant. Product for industrial use only.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

CARBON BLACK (1333-86-4)

WEL TWA (mg/m³) 3.5 mg/m³

WEL STEL (mg/m³) 7 mg/m³

CALCIUM CARBONATE (1317-65-3)

WEL TWA (mg/m³) 10 mg/m³ inhalable dust. 4 mg/m³ respirable dust

SYNTHETIC CRYSTALLINE-FREE GEL (112926-00-8)

WEL TWA (mg/m³) 6 mg/m³ inhalable dust. 2.4 mg/m³ respirable dust

Exclusive British Isles Distributors for Carlisle-SynTec and RubberBond EPDM single ply roofing materials.

Flex-R, Sandwood House, Hillbottom Road, Sands Industrial Estate, High Wycombe, Buckinghamshire, HP12 4HJ. Tel: +44 (0)1494 448792 Fax: +44 (0)1494 858433

5/11





Safety Data Sheet

Two-Part Pourable Sealer – Part A 3.78L

Revision Date: 28/02/2018

8.2. Exposure controls

Appropriate engineering controls	Provide adequate ventilation. Emergency eye wash fountains should be available in the immediate vicinity of any potential exposure.
Personal protective equipment	Avoid all unnecessary exposure.
Eye/face protection	Chemical goggles or face shield. Standard EN 166 - Personal eye-protection.
Hand protection	Wear chemically resistant protective gloves. Standard EN 374 - Protective gloves against chemicals. Gloves should be removed and replaced if there are any signs of degradation or breakthrough.
Other skin and body protection	Long sleeved protective clothing.
Respiratory protection	Not required for normal conditions of use. In case of insufficient ventilation, wear suitable respiratory equipment.
Environmental exposure controls	Avoid release to the environment.
Thermal hazard protection	Wear heat-resistant gloves and clothing if the product is heated.
Other information	Do not eat, drink or smoke during use. Handle in accordance with good industrial hygiene and safety procedures.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Appearance	Viscous.
Colour	Black.
Odour	Slight. Aromatic.
Odour threshold	No data available
pH	No data available
Relative evaporation rate (butylacetate=1)	No data available
Melting point	No data available
Freezing point	No data available
Boiling point	> 260 °C
Flash point	254 °C
Auto-ignition temperature	No data available
Decomposition temperature	No data available
Flammability (solid, gas)	Not applicable

Exclusive British Isles Distributors for Carlisle-SynTec and RubberBond EPDM single ply roofing materials.

Flex-R, Sandwood House, Hillbottom Road, Sands Industrial Estate, High Wycombe, Buckinghamshire, HP12 4HJ. Tel: +44 (0)1494 448792 Fax: +44 (0)1494 858433

6/11





Safety Data Sheet

Two-Part Pourable Sealer – Part A 3.78L

Revision Date: 28/02/2018

Vapour pressure	< 0.001 mm Hg
Relative vapour density at 20 °C	No data available
Relative density	1.23 (Water = 1)
Solubility	Insoluble in water.
Log Pow	No data available
Log Kow	No data available
Viscosity, kinematic	No data available
Viscosity, dynamic	250000 mPa·s
Explosive properties	Not explosive.
Oxidising properties	Not oxidising.
Explosive limits	No data available

9.2. Other information

VOC content	< 15 g/l
-------------	----------

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	Stable under normal conditions.
------------	---------------------------------

10.2. Chemical stability

Stability	Stable under normal conditions.
-----------	---------------------------------

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	None known
------------------------------------	------------

10.4. Conditions to avoid

Conditions to avoid	Extremely high or low temperatures.
---------------------	-------------------------------------

10.5. Incompatible materials

Materials to avoid	Strong oxidizing agents. Strong acids. Strong alkalis.
--------------------	--

10.6. Hazardous decomposition products

Hazardous decomposition products	Fire may produce irritating, corrosive and/or toxic gases. Butadiene. calcium oxides. Carbon monoxide. Carbon dioxide.
----------------------------------	--

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	Not classified
----------------	----------------

Exclusive British Isles Distributors for Carlisle-SynTec and RubberBond EPDM single ply roofing materials.

Flex-R, Sandwood House, Hillbottom Road, Sands Industrial Estate, High Wycombe, Buckinghamshire, HP12 4HJ. Tel: +44 (0)1494 448792 Fax: +44 (0)1494 858433

7/11





Safety Data Sheet

Two-Part Pourable Sealer – Part A 3.78L

Revision Date: 28/02/2018

Based on available data, the classification criteria are not met

Toxicological information on ingredients.

1,1'-Phenyliminodipropan-2-ol (3077-13-2)

LD50 oral rat 3763 mg/kg
LD50 dermal rabbit > 2000 mg/kg

Skin corrosion/irritation Not classified
Based on available data, the classification criteria are not met

Serious eye damage/irritation Not classified
Based on available data, the classification criteria are not met

Respiratory or skin sensitisation Not classified
Based on available data, the classification criteria are not met

Germ cell mutagenicity Not classified
Based on available data, the classification criteria are not met

Carcinogenicity May cause cancer.

Reproductive toxicity Suspected of damaging the unborn child.

Specific target organ toxicity (single exposure) Not classified
Based on available data, the classification criteria are not met

Specific target organ toxicity (repeated exposure) Causes damage to organs (adrenal glands, bone marrow, liver, kidneys, lymphoid system, stomach, thymus) through prolonged or repeated exposure (in contact with skin).

Aspiration hazard Not classified
Based on available data, the classification criteria are not met

Potential adverse human health effects and symptoms May cause slight irritation to eyes. May cause slight irritation to the skin. Ingestion may cause irritation of the gastrointestinal tract. Inhalation of vapours may cause respiratory irritation.

SECTION 12: Ecological Information

12.1. Toxicity

Ecology - water Not classified.

RESIDUAL OILS (PETROLEUM,) SOLVENT-REFINED (64742-01-4)

LC50 > 5000 mg/l (96 Hours, Oncorhynchus mykiss (Rainbow trout))
EC50 > 1000 mg/l (96 Hours, Daphnia magna)

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

Exclusive British Isles Distributors for Carlisle-SynTec and RubberBond EPDM single ply roofing materials.

Flex-R, Sandwood House, Hillbottom Road, Sands Industrial Estate, High Wycombe, Buckinghamshire, HP12 4HJ. Tel: +44 (0)1494 448792 Fax: +44 (0)1494 858433





Safety Data Sheet

Two-Part Pourable Sealer – Part A 3.78L

Revision Date: 28/02/2018

12.4. Mobility in soil

RubberBond Two-Part Pourable Sealer – Part A

Ecology - soil Insoluble in water.

12.5. Results of PBT and vPvB assessment

RubberBond Two-Part Pourable Sealer – Part A

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Other adverse effects

Other adverse effects Avoid release to the environment

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods Dispose of this material and its container at hazardous or special waste collection point.

Waste disposal recommendations Allow product to cure before disposal. Dispose in a safe manner in accordance with local/national regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

Additional information Handle empty containers with care.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR) Not regulated for transport

UN-No. (IATA) Not regulated for transport

UN-No. (IMDG) Not regulated for transport

14.2. UN proper shipping name

Not applicable

14.3. Transport hazard class(es)

Not applicable

14.4. Packing group

Not applicable

14.5. Environmental hazards

Exclusive British Isles Distributors for Carlisle-SynTec and RubberBond EPDM single ply roofing materials.

Flex-R, Sandwood House, Hillbottom Road, Sands Industrial Estate, High Wycombe, Buckinghamshire, HP12 4HJ. Tel: +44 (0)1494 448792 Fax: +44 (0)1494 858433

9/11





Safety Data Sheet

Two-Part Pourable Sealer – Part A 3.78L

Revision Date: 28/02/2018

Other information

No supplementary information available.

14.6. Special precautions for user

Special transport precautions

No special precautions required.

14.6.1. Overland transport

No additional information available

14.6.2. Transport by sea

No additional information available

14.6.3. Air transport

No additional information available

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Authorisations and/or restrictions on use (Annex XVII):

RubberBond Two-Part Pourable Sealer – Part A

3.b. Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10

Contains no substance on the REACH candidate list

VOC content < 15 g/l

15.1.2. National regulations

National regulations No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Issued by Technical

Revision date 28/02/2018

Data sources REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and

Exclusive British Isles Distributors for Carlisle-SynTec and RubberBond EPDM single ply roofing materials.

Flex-R, Sandwood House, Hillbottom Road, Sands Industrial Estate, High Wycombe, Buckinghamshire, HP12 4HJ. Tel: +44 (0)1494 448792 Fax: +44 (0)1494 858433

10/11





Safety Data Sheet

Two-Part Pourable Sealer – Part A 3.78L

Revision Date: 28/02/2018

Hazard statements in full

packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Asp. Tox. 1 Aspiration hazard, Category 1
Carc. 1B Carcinogenicity, Category 1B
Eye Irrit. 2 Serious eye damage/eye irritation, Category 2
Repr. 2 Reproductive toxicity, Category 2
Skin Irrit. 2 Skin corrosion/irritation, Category 2
STOT RE 1 Specific target organ toxicity — Repeated exposure, Category 1
H304 May be fatal if swallowed and enters airways
H315 Causes skin irritation
H319 Causes serious eye irritation
H350 May cause cancer
H361d Suspected of damaging the unborn child
H372 Causes damage to organs through prolonged or repeated exposure

NCEC SDS EU (REACH ANNEX II)

The information contained herein is based upon data and information available to us, and reflects our best professional judgment. This product may be formulated in part with components purchased from other companies. In many instances, especially when proprietary or trade secret materials are used, CCWI Company must rely upon the hazard evaluation of such components submitted by that product's manufacturer or importer. No warranty of merchantability, fitness for any use, or any other warranty is expressed or implied regarding the accuracy of such data or information. The results to be obtained from the use thereof, or that any such use does not infringe any patent, since the information contained herein may be applied under conditions of use beyond our control and with which we may be unfamiliar, we do not assume responsibility for the results of such application. This information is furnished upon the condition that the person receiving it shall make his own determination of the suitability of the material for his particular use

Exclusive British Isles Distributors for Carlisle-SynTec and RubberBond EPDM single ply roofing materials.

Flex-R, Sandwood House, Hillbottom Road, Sands Industrial Estate, High Wycombe, Buckinghamshire, HP12 4HJ. Tel: +44 (0)1494 448792 Fax: +44 (0)1494 858433

11/11

