



Safety Data Sheet

WBA Deck Adhesive – 5L / 15L Pail

Revision Date: 14/02/2018

Section 1: Identification of the Product and Company Identification

1.1. Product Identifier

Product Name: RubberBond WBA Deck Adhesive Pail
Product Code: 521003 / 521002

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Adhesive
Uses advised against No specific uses advised against are identified.

1.3. Details of the supplier of the safety data sheet

Suppliers: Flex-R
Sandswood House
Hillbottom Road
Sands Industrial Estate
High Wycombe
Buckinghamshire
HP12 4HJ
Tel: 01494 448792 Fax: 01494 858433 Email: enq@rubberbond.co.uk

1.4. Emergency telephone number

Emergency telephone 01494 448792 (NOT 24HRS Monday-Thursday 08.30 – 17.30
Friday 08.30 – 16.30)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified
Health hazards Not Classified
Environmental hazards Not Classified

2.2. Label elements

Hazard statements NC Not ClassifiedH315

Supplemental label information Treated article incorporates biocidal product <0.1%. active ingredient: tetrahydro-1,3,4,6-tetrakis(hydroxymethyl)imidazo[4,5-d]imidazole-2,5(1H,3H)-dione reaction mass of:5-chloro-2-methyl-4-iso-thiazolin-3-one and 2-methyl-2H-isothiazol-3-one.(3:1). May produce an allergic reaction

Supplementary precautionary P261 Avoid breathing vapour/ spray.

Exclusive British Isles Distributors for Carlisle-SynTec and RubberBond EPDM single ply roofing materials.

Flex-R, Sandswood House, Hillbottom Road, Sands Industrial Estate, High Wycombe, Buckinghamshire, HP12 4HJ. Tel: +44 (0)1494 448792 Fax: +44 (0)1494 858433





Safety Data Sheet

WBA Deck Adhesive – 5L / 15L Pail

Revision Date: 14/02/2018

statements

P272 Contaminated work clothing should not be allowed out of the workplace.
P321 Specific treatment (see medical advice on this label).
P362+P364 Take off contaminated clothing and wash it before reuse.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

AMMONIA ...%			0.2%
CAS number: 1336-21-6	EC number: 215-647-6 M factor (Acute) = 1	REACH registration number: 01- 2119982985-14-0000	
Classification Acute Tox. 4 - H302 Acute Tox. 2 - H330 Skin Corr. 1B - H314 Eye Dam. 1 - H318 STOT SE 3 - H335 Aquatic Acute 1 - H400			

The Full Text for all Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Remove affected person from source of contamination.
Inhalation	Move affected person to fresh air at once. Get medical attention if any discomfort continues.
Ingestion	DO NOT induce vomiting. Get medical attention immediately.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if any discomfort continues.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention if irritation persists after washing. Show this Safety Data Sheet to the medical personnel.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	No specific symptoms known.
Ingestion	May cause discomfort if swallowed.
Skin contact	Prolonged skin contact may cause redness and irritation.
Eye contact	No specific symptoms known.

Exclusive British Isles Distributors for Carlisle-SynTec and RubberBond EPDM single ply roofing materials.

Flex-R, Sandwood House, Hillbottom Road, Sands Industrial Estate, High Wycombe,
Buckinghamshire, HP12 4HJ. Tel: +44 (0)1494 448792 Fax: +44 (0)1494 858433





Safety Data Sheet

WBA Deck Adhesive – 5L / 15L Pail

Revision Date: 14/02/2018

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with foam, carbon dioxide, dry powder or water fog.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards	Not known.
Hazardous combustion products	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Oxides of carbon. Oxides of nitrogen.

5.3. Advice for firefighters

Protective actions during firefighting	Containers close to fire should be removed or cooled with water. Do not allow water to contact any leaked material.
Special protective equipment for firefighters	Wear chemical protective suit. Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Wear protective clothing as described in Section 8 of this safety data sheet.
-----------------------------	-------------------------------------------------------------------------------

6.2. Environmental precautions

Environmental precautions	Do not discharge into drains or watercourses or onto the ground.
----------------------------------	------------------------------------------------------------------

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	Absorb spillage with non-combustible, absorbent material. Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers and seal securely. Provide adequate ventilation. Contain spillage with sand, earth or other suitable non-combustible material. Avoid the spillage or runoff entering drains, sewers or watercourses.
--------------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

6.4. Reference to other sections

Reference to other sections	Wear protective clothing as described in Section 8 of this safety data sheet.
------------------------------------	-------------------------------------------------------------------------------

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Exclusive British Isles Distributors for Carlisle-SynTec and RubberBond EPDM single ply roofing materials.

Flex-R, Sandwood House, Hillbottom Road, Sands Industrial Estate, High Wycombe, Buckinghamshire, HP12 4HJ. Tel: +44 (0)1494 448792 Fax: +44 (0)1494 858433





Safety Data Sheet

WBA Deck Adhesive – 5L / 15L Pail

Revision Date: 14/02/2018

Usage precautions

No specific recommendations.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Store in closed original container at temperatures between 5°C and 25°C.

Storage class

Unspecified storage.

7.3. Specific end use(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

AMMONIA ...%

Long-term exposure limit (8-hour TWA): WEL 25 ppm vapour

Short-term exposure limit (15-minute): WEL 35 ppm vapour

WEL = Workplace Exposure Limit

Ingredient comments

WEL = Workplace Exposure Limits

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection

The following protection should be worn: Chemical splash goggles.

Hand protection

It is recommended that gloves are made of the following material: Nitrile rubber. It should be noted that liquid may penetrate the gloves. Frequent changes are recommended.

Other skin and body protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact. Wear apron or protective clothing in case of contact.

Hygiene measures

Use engineering controls to reduce air contamination to permissible exposure level. Wash hands after handling. When using do not eat, drink or smoke.

Respiratory protection

Not relevant.

Environmental exposure controls

Keep container tightly sealed when not in use.

SECTION 9: Physical and Chemical Properties

Exclusive British Isles Distributors for Carlisle-SynTec and RubberBond EPDM single ply roofing materials.

Flex-R, Sandwood House, Hillbottom Road, Sands Industrial Estate, High Wycombe, Buckinghamshire, HP12 4HJ. Tel: +44 (0)1494 448792 Fax: +44 (0)1494 858433





Safety Data Sheet

WBA Deck Adhesive – 5L / 15L Pail

Revision Date: 14/02/2018

9.1. Information on basic physical and chemical properties

Appearance	Coloured liquid.
Colour	White/off-white.
Odour	Characteristic.
Odour threshold	Not available.
pH	Not available.
Melting point	Not applicable.
Initial boiling point and range	Not applicable.
Flash point	Technically not feasible.
Evaporation rate	Not applicable.
Evaporation factor	Not available.
Flammability (solid, gas)	Not available.
Other flammability	Not available.
Vapour pressure	Not available.
Vapour density	Not available.
Relative density	1.15 @ 20°C
Bulk density	Not available.
Solubility(ies)	Soluble in water.
Partition coefficient	Not available.
Decomposition Temperature	Not available.
Viscosity	Kinematic viscosity > 20.5 mm ² /s.
Explosive properties	Not available.
Explosive under the influence of a flame	Not considered to be explosive.
Oxidising properties	Not available.
Comments	Information given is applicable to the product as supplied.

9.2. Other information

Other information	No information required.
Refractive index	Not available.
Particle size	Not available.
Molecular weight	Not available.
Volatility	Not available.
Saturation concentration	Not available.
Critical temperature	Not available.

SECTION 10: Stability and reactivity

Exclusive British Isles Distributors for Carlisle-SynTec and RubberBond EPDM single ply roofing materials.

Flex-R, Sandwood House, Hillbottom Road, Sands Industrial Estate, High Wycombe, Buckinghamshire, HP12 4HJ. Tel: +44 (0)1494 448792 Fax: +44 (0)1494 858433





Safety Data Sheet

WBA Deck Adhesive – 5L / 15L Pail

Revision Date: 14/02/2018

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Not applicable. Not relevant.

10.4. Conditions to avoid

Conditions to avoid Avoid freezing.

10.5. Incompatible materials

10.6. Hazardous decomposition products

Hazardous decomposition products Does not decompose when used and stored as recommended.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity – inhalation

ATE inhalation (vapours mg/l) 700.0

Toxicological information on ingredients.

AMMONIA ...%

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 350.0

Species Rat

ATE oral (mg/kg) 350.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 1.4

Species Rat

ATE inhalation (vapours mg/l) 1.4

SECTION 12: Ecological Information

12.1. Toxicity

Exclusive British Isles Distributors for Carlisle-SynTec and RubberBond EPDM single ply roofing materials.

Flex-R, Sandwood House, Hillbottom Road, Sands Industrial Estate, High Wycombe, Buckinghamshire, HP12 4HJ. Tel: +44 (0)1494 448792 Fax: +44 (0)1494 858433





Safety Data Sheet

WBA Deck Adhesive – 5L / 15L Pail

Revision Date: 14/02/2018

Ecological information on ingredients.

AMMONIA ...%

Acute aquatic toxicity

LE(C)₅₀ 0.1 < L(E)C₅₀ ≤ 1

reaction mass of: 5-chloro-2-methyl-4-iso-thiazolin-3-one-and 2-methyl-2H-isothiazol-3-one

Acute aquatic toxicity 350.0

LE(C)₅₀ 0.1 < L(E)C₅₀ ≤ 1

M factor (Acute) 1

Chronic aquatic toxicity

M factor (Chronic) 1

12.2. Persistence and degradability

12.3. Bioaccumulative potential

Partition coefficient Not available.

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

Exclusive British Isles Distributors for Carlisle-SynTec and RubberBond EPDM single ply roofing materials.

Flex-R, Sandwood House, Hillbottom Road, Sands Industrial Estate, High Wycombe, Buckinghamshire, HP12 4HJ. Tel: +44 (0)1494 448792 Fax: +44 (0)1494 858433





Safety Data Sheet

WBA Deck Adhesive – 5L / 15L Pail

Revision Date: 14/02/2018

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Health and Safety at Work etc. Act 1974 (as amended).
The Control of Substances Hazardous to Health Regulations 2002 (SI 2002 No. 2677) (as amended).
Control of Substances Hazardous to Health Regulations 2002 (as amended).

EU legislation

Commission Directive 91/322/EEC of 29 May 1991 on establishing indicative limit values by implementing Council Directive 80/1107/EEC on the protection of workers from the risks related to exposure to chemical, physical and biological agents at work.
Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Issued by

Technical

Revision date

01/06/2017

Hazard statements in full

H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H361f Suspected of damaging fertility.
H373 May cause damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.

Exclusive British Isles Distributors for Carlisle-SynTec and RubberBond EPDM single ply roofing materials.

Flex-R, Sandwood House, Hillbottom Road, Sands Industrial Estate, High Wycombe, Buckinghamshire, HP12 4HJ. Tel: +44 (0)1494 448792 Fax: +44 (0)1494 858433





Safety Data Sheet

WBA Deck Adhesive – 5L / 15L Pail

Revision Date: 14/02/2018

Store Between

Store Between 5°C - 25°C

Contains SVHC

NO

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.

Exclusive British Isles Distributors for Carlisle-SynTec and RubberBond EPDM single ply roofing materials.

Flex-R, Sandwood House, Hillbottom Road, Sands Industrial Estate, High Wycombe,
Buckinghamshire, HP12 4HJ. Tel: +44 (0)1494 448792 Fax: +44 (0)1494 858433

9/9

